

## Specification

Model	808D-300-5.6-BL
Output Power	300mw
Wavelength	808nm
working voltage	DC 1.9V
working current	400mA
working temperature	-10°~+40°
working life	>10000h
Dimensions	TO-18 (5.6mm)


### LJ808LD300 -H4T 808nm 300mW 40°C Laser Diodes

#### ■ Specifications

Wavelength:	808nm
Light Output:	300mW CW
Package Type:	TO-18(Φ 5.6mm)

#### ■ Absolute Maximum Ratings (Tc=25°C)

Parameter	Symbols	Ratings	Units
Optical Output	Po(CW)	300	mW
Reverse Voltage	Vr	2	V
Operating Temperature	Top	-10 ~ +40	°C
Storage Temperature	Tstg	-40 ~ +80	°C



#### ■ Electrical and optical Characteristics(Tc=25°C)

Parameter	Symbols	Conditions	Min	Typ	Max	Units	
Threshold Current	Ith	-	-	50	70	mA	
Operating Current	Iop	Po=300mW	-	350	370	mA	
Operating Voltage	Vop	Po=300mW	-	1.8	2.1	Volts	
Slope		-					
Efficiency	$\eta$	-	0.8	1.0	-	mW/mA	
Beam Divergence (FWHM)	Parallel	$\theta \parallel$	Po=300mW	9	12	15	deg
	Perpendicular	$\theta \perp$	Po=300mW	28	30	35	deg
Parallel Deviation Angle	$\Delta \theta \parallel$	Po=300mW	-3	-	3	deg	
Perpendicular Deviation Angle	$\Delta \theta \perp$	Po=300mW	-3	-	3	deg	
Emission Point Accuracy	$\Delta X, \Delta Y, \Delta Z$	Po=300mW	-80	-	80	um	
Lasing Wavelength	$\lambda_p$	Po=300mW	805	808	811	nm	

Im is sorting by custom's need

©  $\theta \parallel$  and  $\theta \perp$  are defined as the angle within which the intensity is 50% of the peak value.